

TLM - 404 4" x 4 TFT LCD Monitor



The TLM - 404 includes four 4" TFT LCD monitor in a standard 19" rack mount, 2 RU high. It can tilt to +/- 30 degrees and lock in any position. Controls include contrast, brightness, color and tint. (Tint is NTSC only). Composite video in with 75 ohm self terminating pass through. Three tally LED's per screen.



LCD Display

4" TFT LCD, active matrix, 480 x 234 Pixels, 300 candle luminance backlight

Video Input

Composite Video 1.0 Vp-p, 75 ohm

Video Output

Loop-through with 75 ohm self terminated, 1.0 Vp-p output at 75 ohm load

Power Consumption

DC 12 Volt. 50 Watts
35 Watts for LCDs display, 15 Watts for Aux adaptor

Power Supply

AC 90 - 240 Volt input, DC 12 Volt 50 Watts output

Video System

NTSC/PAL auto recognition

Dimensions

Standard 19" rack mounting size

Accessories (Included)

Allen Wrench (1.5 mm)
Allen Wrench (2.5 mm)
Instruction Manual (1)
BNC Cable (4)
Power Adaptor (1)
Power Cord (1)



Holder for SE - 800



STRONG, LOCKING PIVOT POINT



Tally and Aux In connectors

datavideo®

Datavideo Corporation
12300 E. Washington Blvd., Suite U
Whittier, CA 90606 U.S.A.
Tel. 562-696-2324
E-mail: contactus@datavideo-tek.com
<http://www.datavideo-tek.com>

Datavideo Technologies Co., Ltd.
10F, No. 176, Jian-Yi Rd., Chung Ho City,
Taipei Hsien 235, Taiwan, R.O.C.
Tel. 886-2-8227-2888
E-mail: info@datavideo.com.tw
<http://www.datavideo.com.tw/>

Datavideo Technologies Europe BV
Californiedreef 26, 3565 BL Utrecht,
The Netherlands
Tel. +31 30 261 9656
E-mail: info@datavideo.nl
<http://www.datavideo.nl/>

Datavideo Technologies China Co., Ltd.
2F-D, No. 2, Lane 777, West Guangzhong Rd.,
Zhabei District, Shang-Hai, China
Tel. 886-21-56036599
E-mail: info@datavideo.cn
<http://www.datavideo.cn>